



Date : June 18, 2009



■ Feature:

- Universal input 90~264VAC or 127~375VDC
- Active PFC > 0.95
- Current share 3+1 up to 4KW
- Inrush current limit soft start function
- Over voltage, over load and over temp protection
- Short circuit shutdown and auto recovery
- Output voltage remote sense
- Remote control ON/OFF
- Power good signal
- UL, cUL, TUV, CB, CE pend
- 3 years warranty
- Dimension : 295 x 127 x 40.6 mm

Here is the shortcut of **1000W** single output unit, **SPS-1000P** series for reference

Electronic function:

- ** **Current share function for parallel use up to 4KW (3+1)**. (please refer to the detail spec for the parallel operation)
- ** **High efficiency up to 88% for high output wattage P/S**
- ** **Over temperature protection available.**
- ** **Remote control and remote sensing available**
- ** **Power good signal with high level TTL signal release**
- ** **1U height size (295 x 127 x 40.6mm)**
- ** **Wide operating temperature from -20deg.C to 70deg.C.**(please refer to the detail spec)

Safety:

Complied to EN61000-3-2 Class D standard.

UL, cUL, **TUV EN60950-1:2006** pending (**CB certificate will be available by week 26**).

New CE directive conformity (**LVD 2006/95/EC** and **EMS 2004/108/EC**) is available.

Application:

Automatic control system
General electronic system

For more info, please feel free to contact your sales representative.